


Mass fusion splicer
for up to 12 fibre ribbon

TYPE-71M12



**Industry only dual independent heaters and
Auto Clamping Adjustment System "ACAS"**



Two Independent
Heaters for
High Productivity



Touch Screen
Control Panel



Durable & Rugged

Specifications		
Items		TYPE-71M12
Optical fibre requirements	Material	Silica glass
	Profile types	SMF (G.652), MMF (G.651), DSF (G.653), NZDSF (G.655), BIF (G.657)
	Fibre count	1, 2, 4, 5, 6, 8, 10, 12
	Cladding diameter	125µm
	Coating diameter	Single fibre coating dia: 250µm, 500µm, 900µm Ribbon fibre thickness: 250-400µm
	Applicable cable	Drop cable (2.0mm×3.1 or 2.6mm), Indoor cable (2.0mm×1.6mm)
Standard performance	Cleave length	10mm
	Splice loss (typical) *1	SMF:0.05dB, MMF:0.02dB, DSF:0.08dB, NZDSF:0.08dB
	Splice time (typical)	9sec (with single SMF) 14sec (with 12C SMF)
	Heating time (typical)	Approx. 55 sec (with FPS-6 sleeve)
	Splice & heat cycles per battery full charge *2	Approx. 110 (with BU-11)
	Fibre view and magnification	2 CMOS cameras observation, 23X (zoom : 46X)
Proof test	Proof test	1.96N -2.09N
Programs	Splice programs	Max. 200
	Heating programs	Max. 100
Functions	Splice image capture / Splice data storage	64 images/10,000 splices
	Onboard user training video	Provided
	Auto-start	Splice/Heating
	Automatic arc calibration	Automatically compensates for environmental condition change
	Auto clamping adjustment system	Provided
	Reversible fibre holder system	Provided
	Dual automatic independent heaters	Provided
	User-selectable heater clamp operation	Provided
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
	Automatic fibre count detection	Provided
	Remote interactive maintenance	Provided
Size / Weight	Size	120 (W) x 154 (D) x 130 (H) mm (without anti-shock rubber)
	Weight	1.7kg (without Battery) / 1.9kg (with Battery BU-11S) / 2.0kg (with Battery BU-11)
	Monitor	4.1 inch color LCD monitor with touchscreen
Terminals	DC output	DC 12 V (for JR-6)
	USB port	USB2.0 mini-B
	Storage media	SD and SDHC
Power supply	AC input	100-240V, 50/60Hz
	DC input	10-15V, 4.5A
	Battery pack	Li-ion 11.1V, 4,600mAh (BU-11)
Operating condition		Altitude: 0 to 3,660 m, Temperature: -10°C to +50°C, Humidity: 0% to 95% (non-condensing), Wind velocity: up to 15 m/s
Storage condition		Temperature: -40°C to +80°C, Humidity: 0% to 95% (non-condensing), Battery: -20 - +30°C (long term)
Electrode life *3		1,500 arcs discharges
Software updates		Internet
Data management		Can be stored, edited and analyzed by dedicated PC software

*1 : With Sumitomo identical fibres(in room temperature). Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Electrode life may vary depending on the operating environment.


Environmental Durability*	
	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Water resistance	Equivalent to IPx2 (Operates normally after being exposed to water dripping at 3mm/min, for at least 2.5 min on each of 4 surfaces tilted at 15°)
Dust resistance	Equivalent to IP5x (Operates normally after 8 hours in a test chamber with circulating dust particles smaller than 75µm)

*Confirms the battery operation in tests carried out by Sumitomo.
Does not guarantee that the product is free of faults or damage.

Basic Accessories		
Part name	Part No.	Qty.
AC adapter	ADC-1430 series	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Operating CD manual	—	1 pc
Quick reference guide	—	1 pc
Carrying case with worktable	CC-71+	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

*X=2(USA), 3(EU), 4(JP), 5(UK), 6(AUS), 7(South Africa)

At least, the above basic accessories come with splicer main body.
Some additional accessories may be or may not be included as a splicer standard kit contents. The standard splicer kit contents varies in each region/country.
Please ask details to your nearest distributors.



Drop cable splicing with fibre holder system



Available for Lynx-Custom Fit™ Splice-On Connector



Handy cleaver FC-6R series



Hot jacket remover JR-6



Table-top cleaver FC-6 / FC-6R series

Accessories		
Part name	Part No.	Remarks
Accessories for Splicer	FHS-025	0.25 mm single fibre
	FHS-09	0.9 mm single fibre
	FHD-1	For drop and indoor cables (single fibre)
	FHC-3	3 mm cable
	FHM-2	For 2-fibre ribbon
	FHM-4	For 4-fibre ribbon
	FHM-5	For 5-fibre ribbon
	FHM-6	For 6-fibre ribbon
	FHM-8	For 8-fibre ribbon
	FHM-10	For 10-fibre ribbon
	FHM-12	For 12-fibre ribbon
	Lynx2-UML-S	For ϕ3 mm cord and ϕ0.9 mm single fibre
	Battery pack	BU-11/11S Li-ion 4,600mAh BU-11, 2,300mAh BU-11S
	AC adapter	ADC-1430S For TYPE-71 series and BC-11
	Car battery cable	PCV-11 For car battery operation (cigarette socket type)
Accessories	Electrodes	ER-10 —
	V-groove cleaning jig	VGT-2 Brush for cleaning V-groove
	Battery charger	BC-11 Battery charger for BU-11S/11
	Fibre cleaver	FC-6RM-C Fibre cleaver for single fibre and up to 12-fibre ribbon
	Handheld fibre cleaver	FC-8R-FC/F Handheld fibre cleaver for single fibre and up to 12-fibre ribbon
	Jacket remover	JR-M03 Jacket remover for single fibre
	JR-6	Hot jacket remover for ribbon fibre
	FPS-1	60 mm sleeve for single fibre
	FPS-40	40 mm sleeve for single fibre
	FPS-5	40 mm sleeve for single fibre and up to 8-fibre ribbon
	FPS-6	40 mm sleeve for single fibre and up to 12-fibre ribbon
	FPS-D60	60 mm sleeve for single-fibre drop, and indoor cables
	Alcohol dispenser	HR-3 Alcohol dispenser

SUMITOMO ELECTRIC INDUSTRIES, LTD.

Tokyo (Japan)
Sumitomo Electric Industries, Ltd.
 Akasaka Center Building, 1-3-13, Motoakasaka,
 Minato-ku, Tokyo, 107-8468, JAPAN
 TEL: +81-3-6406-2666
<http://global-sei.com/sumitomo-electric-splicers>

London (U.K.)
Sumitomo Electric Europe Ltd.
 220 Centennial Park, Centennial Avenue,
 Elstree, Herts. WD6 3SL, U.K.
 TEL: +44 20-8953-8118
<http://www.sumielectric.com/>

Dubai (U.A.E.)
Middle east office
 Dubai Airport Free Zone Phase 4WA,
 Office 702 P.O. Box 54890, Dubai, UAE
 TEL: +971 4-701-7338

Melbourne (Australia)
SWS Australia Pty. Limited
 Oceania representative office
 23 Scanlon Drive, Epping, Victoria,
 3076, AUSTRALIA
 TEL: +61 3-8401-2800